

OD LITE SEALER

OD Lite Sealer is an alkali resisting primer for concrete and cement plaster surface. It is ideally suited for use as a primer (sealer) on difficult areas like porous and chalking surfaces in order to increase the strength of the surface for paint coating.

PHYSICAL DATA

Colour	White
Gloss	Flat
Solid (By Volume)	40%
Specific gravity	1.30
Flash point	Nil
Viscosity	100 K.U.

RECOMMENDATION FOR USE

Film thicknesses	Dry	:	35 microns
------------------	-----	---	------------

	Wet	:	88 microns
--	-----	---	------------

Theoretical spreading rate at recommended film thickness	11 - 12 m ²
--	------------------------

Practical spreading rate (with a loss factor of 20%)	8 - 9 m ²
--	----------------------

Drying time (guiding data at ambient condition)

Dry to touch	25 MIN
--------------	--------

Dry to recoat, min	2 hours
--------------------	---------

Dry to handle, min	4 hours
--------------------	---------

Application methods	Brush, roller or spray-gun
---------------------	----------------------------

Guiding data for airless spray equipment

Nozzle tip	-
------------	---

Spray angle	-
-------------	---

Hydraulic pressure	-
--------------------	---

Thinner/cleaner	Water
-----------------	-------

Surface preparation	Porous and/ or chalking surfaces should be brushed off prior to application of OD Lite Sealer.
---------------------	--

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under conditions beyond our control, we cannot guarantee anything but the quality of the paint itself.

We reserve the right to change the given data without notice.