

OD LUX

OD Lux is a high quality alkyd gloss enamel for use as a topcoat on most types of exterior and interior surfaces such as steel and woodwork. It contains active fungicides and will thus prevent mould growth. OD Lux has excellent gloss and colour retention as well as outstanding durability. It has good covering capacity.

PHYSICAL DATA

Colour	According to colour card
Gloss	Gloss Finish
Solid (By Volume)	50%
Specific gravity	10 – 1.2
Flash point	40°C - 104°F
Viscosity	70 - 74 K.U.

RECOMMENDATION FOR USE

Film thicknesses	Dry : 30 microns – 1.2 mils Wet : 60 microns – 2.4 mils
Theoretical spreading rate at recommended film thickness	17 m ²
Practical spreading rate (with a loss factor of 20%)	12 - 14 m ²
Drying time (guiding data at ambient condition)	
Dry to touch	2.5 hours
Dry to recoat, min	12 hours
Dry to handle, min	24 hours
Application methods	Brush, roller or spray-gun (conventional)
Turpentine /cleaner	Turpentine
Surface preparation	The surfaces must be dry and clean during application. New surface must first be appropriately primed/ sealed before applying OD Lux as a topcoat. Old painted surface must be rid of loose or flaking paint film before hand.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under conditions beyond our control, we cannot guarantee anything but the quality of the paint itself.

We reserve the right to change the given data without notice.