

OD SILK (Luxury Glo Finish)

OD Silk is a premium quality emulsion paint based on a special Vinyl Acrylic binder. It has excellent flow and forms a smooth film with a luxurious sheen. Ideal for interior use, OD Silk gives excellent durability and beauty and has good covering capacity. Excellently suited as topcoat.

PHYSICAL DATA

Colour	According to colour card
Gloss	High Sheen
Solid (by volume)	47%
Specific gravity	1.20 – 1.35
Flash point	Not applicable (water-based)
Viscosity	105 – 108 K.U.

RECOMMENDATION FOR USE

Film thicknesses	Dry : 35 microns Wet : 73 microns
Theoretical spreading rate at recommended film thickness	13.5 m ²
Practical spreading rate (with a loss factor of 18%)	10 – 11 m ²
Drying time (guiding data at ambient condition)	
Dry to touch	25 – 35 min
Dry to recoat, min	2 hours
Dry to handle, min	3 – 6 hours
Application methods	Brush, roller or spray-gun
Guiding data for airless spray equipment	
Hydraulic pressure	150 – 200 Kg./sq.cm.
Nozzle tip	0.021"
Spray angle	65 - 80°
Thinner/cleaner	Water
Surface preparation	New surfaces should be dry clean and sound. Old, porous and/or chalking surfaces should be brushed, cleaned and sealed with a coat of OD Shield Primer prior to application of OD Silk. Any loose old film should be scraped off before hand.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under conditions beyond our control, we cannot guarantee anything but the quality of the paint itself.

We reserve the right to change the given data without notice.